



Automobile & Industrial Oil



### Superior Engine Protection 20w40

DESCRIPTION : Exceeds requirements of API CH-4 and IS 13656 : 2002 EDL - 4 performance standards.

APPLICATIONS : Specially developed multigrade engine oil for use in Tata Ace, Piaggio Ape, Mahindra Champ, Force Minidor, Atul Shakti, Bajaj Auto Rickshaw and other high performance new generation diesel engines of LCVs.

BENEFITS : Possesses extra tackiness that minimizes engine wear even under heavy loads and high operating temperatures.

Packing : 500 ml, 1 ltr, 3 ltr, 3.5 ltr, 5 ltr, 7.5 ltr, 10 ltr, 50 ltr, 210 ltr



### One Plus High Tech Power 4T 20w4

Description : Viscometrics - SAE 20w40 # Exceeds API SM and JASO MA2 performance levels

Applications : Special formulated multi grade oil for engine oil, transmission and wet clutch of 4-strook two-wheelers. # Recommended for Honda, Hero, Bajaj, TVS, Yamaha and suzuki.

Benefits : Ensure excellent, wear protection ▶ Longer drain intervals ▶ Lower clutch shippage ▶ Provides better fuel economy.

Packing : 500 ml, 1 ltr, 3 ltr, 3.5 ltr, 5 ltr, 7.5 ltr, 10 ltr, 50 ltr, 210 ltr



### Hydraulic Oil System 68

Description : ISO VG 68 Grade Meets IS 10522-1983 (Reaffirmed 2004) specification.

Recommended : Antiwear hydraulic and circulating oil specially formulated for efficient lubrication of industrial equipment. Provides long service life due to excellent resistance to oxidation. Protects agains rust and corrosion. Provides good wear protection. Has reduced tendency to foam thereby minimizes noisy operations and erratic actuator response. Change oil as per manufacturers' recommendation.

Packing : 26 ltr, 50 ltr, 210 ltr



### SEMI SYNTHETIC Cutting Oil

Recommended : Cutting fluid is a type of coolant and lubricant designed specifically for metalworking processes, such as machining and stamping. There are various kinds of cutting fluids, which include oils, oil-water emulsions, pastes, gels, aerosols (mists), and air or other gases.

Performance Benefits : Reduction in Operating Costs. ▶ Life improved Quality of Workpiece. ▶ Extension in the Tool. ▶ Higher Feeds and Cutting Speeds ▶ Reduction in the Need of Post-Process Heat Treatments.

Packing : 26 ltr, 50 ltr, 210 ltr

## Pump Set Oil

- Monograd Diesel Engine Pump Set Oil for 20w40
- Enquivalent to : IS 496
- Formulated from Selected Base Oil and Blended with Special
- Additives to Keeps the Pump Set Clean & Cool
- Lower Maintenance
- Recommended for Agricultural Pump Sets Operating on Diesel / L.d.O.

Packing : 3.5 ltr, 5 ltr, 10 ltr



## Shocker Oil

Bajaj, TVS, Yamaha, Honda, Hero, Suzuki Bikes

JMP Super Shocker Oil is ideal for Hydraulic ▶ Front Fork of All Motorcycle to Provide ▶ Excellent Tampering Characteristic.

Packing : 350 ml, 175 ml



## Engine Oil 20W50 Petrol & CNG

JMP Super Gear Oil 20W50 multi grade engine oil provides ease of cold starting due to very high viscosity index, Due to high detergency and excellent oxidation stability it resists decomposition in service to high temperature zone temperatures. Meets the requirement of API SG, IS : 13656-2002 type EPLI/EDLI specifications.

**Recommended for :** All modern petrol and gas engine. **Warning :** Do not fill container with fuel/solvent static could cause fire. Avoid prolonged and repeated skin contact with used oils. Keep out of reach of children. Protect the

**Environment :** Dispose of used lubricants in a responsible manner. Do not pollute drains, water, ways or the soil.

Packing : 500 ml, 1 ltr, 3 ltr, 3.5 ltr, 5 ltr



## All Purpose AP-3 Grease

JMP All purpose grease is having excellent structure stability. Excellent load treating capacity and improved anti-wear corrosion property. It is recommended for all heavy duty equipment and industrial applications.

Excellent protection from wear & corrosion Stable consistency at very high temperature Complete resistance from water wash out prevention of leakage onto brake timing.

Grease after use should be properly disposed off to avoid any harm to the environment. Used grease contains potentially harmful contaminants and hence prolonged or repeated skin contact should be avoided.

Packing : 100 gm, 200 gm, 500 gm, 1 kg, 2 kg, 3 kg, 5 kg, 18 kg, 180 kg





### Superior Engine Protection 15w40



DESCRIPTION : Exceeds requirements of API CH-4 and IS 13656 : 2002 EDL - 4 performance standards.

APPLICATIONS : Specially developed multigrade engine oil for use in Tata Ace, Piaggio Ape, Mahindra Champ, Force Minidor, Atul Shakti, Bajaj Auto Rickshaw and other high performance new generation diesel engines of LCVs.

BENEFITS : Possesses extra tackiness that minimizes engine wear even under heavy loads and high operating temperatures.

Packing : 500 ml, 1 ltr, 3 ltr, 3.5 ltr, 5 ltr, 7.5 ltr, 10 ltr, 50 ltr, 210 ltr

### Gear Oil 90 / 80w90



Description : MP Gear Oil 80w90 oils are an extreme pressure hypoid gear oil. This oil is blended from selected base stocks and contain specific additive package to provide extreme pressure anti wear characteristics.

Applications : 80w90 oils are recommended for all types of heavy & light gears.

Benefits : Satisfy the lubrication requirements of a wide variety of gears. Provide protection against wear, due to good EP characteristic. Give lone service life even under high temperature operation since it has excellent oxidation stability. Provide good protection against corrosion.

Packing : 500 ml, 1 ltr, 3 ltr, 3.5 ltr, 5 ltr, 7.5 ltr, 10 ltr, 50 ltr, 210 ltr

### Steering Oil ATF TQ



Description : DESCRIPTION : JMP Super TQ is automatic transmission fluid specially developed to meet the General Motors specification Type A-Suffix A.

All vehicles fitted with automatic transmission & power steering where Type A Suffix A fluid is recommended. All new generation automotive vehicles fitted with synchromesh gear boxes & power steering gear boxes.

Features : Reduces friction and where even in extreme pressure. Low temperature fluidity. Good stability and resistance to foaming. Good thermal & oxidation resistance. Protection against corrosion.

Packing : 500 ml, 1 ltr.

## JAYMANGAL PETROCHEM PVT. LTD.

(AN ISO 9001 : 2015 Certified Company)

S. No. 136/1, Pune Nashik Road, Bhosari, Pune - 411 039.

Cust. Ca. No. : +91 80879 97599

Email : sales@jaymangalpetrochem.com • Web : www.jaymangalpetrochem.com